Zinc Repair Spray LZ-16

Repair spray for galvanised surfaces.



Product description

Application range	For decorative touching up hot-dip galvanised surfaces and for colour adaptation of extension parts to the galvanised environment.
Properties	• different shades • easy application • fast drying • high covering power
Delivery sizes	aerosol can 400 ml
Application rate	approx. 3 m² / 400 ml can
Colour shades	Available in different shades from light to dark, see ReiColor colour chart no. 195.
Storage stability / shelf-life	Min. 1 year from delivery at room temperature and dry storage.
Flash point	below + 21°C

Handling

Application method	spraying
Working instruction	Before use, shake until rattling sound of stir body can be heard. Maintain spraying distance of approx. 30 cm! Spray in different thin layers, respecting drying time in-between single layer. To avoid plugging of nozzle, spray after use with nozzle down till just gas blows out.
Substrate preparation	Clean well, do not spray on dirt, grease or moisture.
Drying method	air drying
Dry film thickness	approx. 20 µm per application

Over-paintable	not suitable

Notes

Hazard notes	Please observe technical data sheet and safety data sheet before use.

Data base: All technical information in this data sheet is based on laboratory tests and may deviate from values actually resulting from practical use.

Disclaimer: The above data are based on our present knowledge and experience provided that the material is stored properly and applied appropriately. The data are exclusively intended to describe the products and do not constitute warranted properties in any legal sense. We reserve the right to make changes to product specifications at any time. Our technical advice - whether verbal, in writing or by way of trials - is given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release the customer from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

The current version of the technical data sheet with the newest release date is available on our homepage www.reicolor.de/Produkte. With the publication of a new edition of this technical data sheet all information in previous data sheets is no longer valid.

Reicolor Chemie-GmbH
Werkstraße 19 + 21
D-90518 Altdorf b. Nürnberg
Tel.: +49(0)9187/97 03-0
https://www.reicolor.de
info@reicolor.de

Zertifiziertes QM-System DIN EN ISO 9001:2015

Release date: 10.02.2025